

View Online at <https://aerobasegroup.com/nsn/3120-00-198-2239>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.6250 inches

Shank Style:

Externally threaded

Overall Length:

3.8600 inches

Bore Diameter:

0.3750 inches

Overall Outside Diameter:

1.6600 inches

Lubrication Material:

Grease

Shank Thread Length:

1.7500 inches

Outer Ring Width:

0.5500 inches

Inner Ring Width:

0.8120 inches

Length From Bore Center To Shank End:

Between 3.0150 inches and 3.0450 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

18

Thread Size:

0.625 inches

Self-alignment Angle:

10.00 degrees

Special Features:

With flush type lubricator

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel snap ring

Material Specification:

Qq-s-763 federal specification single material response shield

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.