

View Online at <https://aerobasegroup.com/nsn/3120-00-204-4741>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 1.7755 inches and 1.8180 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Outer Member Outside Diameter:**

Between 0.7710 inches and 0.8160 inches

**Bore Center To Shank End Distance:**

Between 1.3900 inches and 1.4100 inches

**Outer Member Width:**

Between 0.3320 inches and 0.3420 inches

**Inner Member Width:**

Between 0.4350 inches and 0.4370 inches

**Shank Thread Length:**

Between 0.8100 inches and 0.9000 inches

**Static Radial Load Rating:**

5000 pounds

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

56.0 rockwell c inner member

**Special Features:**

Std nas keyway in shank, 0.0005 in. Min 0.0015 in. Maximum diametral clearance

**Material:**

Stainless steel rod end body

**Surface Treatment:**

Chromium inner member

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0