

View Online at <https://aerobasegroup.com/nsn/3120-00-204-4741>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 1.7755 inches and 1.8180 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

Between 0.7710 inches and 0.8160 inches

Bore Center To Shank End Distance:

Between 1.3900 inches and 1.4100 inches

Outer Member Width:

Between 0.3320 inches and 0.3420 inches

Inner Member Width:

Between 0.4350 inches and 0.4370 inches

Shank Thread Length:

Between 0.8100 inches and 0.9000 inches

Static Radial Load Rating:

5000 pounds

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

56.0 rockwell c inner member

Special Features:

Std nas keyway in shank, 0.0005 in. Min 0.0015 in. Maximum diametral clearance

Material:

Stainless steel rod end body

Surface Treatment:

Chromium inner member

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0