NSN 3120-00-222-9866

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-222-9866

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 0.2600 inches and 0.2700 inches

**Body Outside Diameter:** 

Between 0.6257 inches and 0.6265 inches

**Body Inside Diameter:** 

Between 0.4840 inches and 0.4910 inches

Flange Outside Diameter:

Between 0.7400 inches and 0.7600 inches

Flange Width:

Between 0.0550 inches and 0.0600 inches

**Corner Shape:** 

Undercut left flange body corner

Surface Finish:

63.0 microinches outside diameter surface of body

Material

Copper alloy 606 or copper alloy 614 or copper alloy 630 or copper alloy 642

**Material Specification:** 

Qq-c-465 federal specification all material responses

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Style Designator:** 

Solid, external flange one end

**Specification Data:** 

80205-nas538 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A045a0