NSN 3120-00-226-1813

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-226-1813

| View Online at https://aerobasegroup.com/nsn/3120-00-226-1813 |
|---|
| Overall Length: |
| Between 2.4904 inches and 2.4954 inches |
| Body Outside Diameter: |
| Between 0.6886 inches and 0.6895 inches |
| Body Inside Diameter: |
| Between 0.4926 inches and 0.4946 inches |
| Corner Shape: |
| Square all corners |
| Hardness Rating: |
| 33.0 rockwell c and 37.0 rockwell c |
| Surface Finish: |
| 200.0 microinches inside diameter surface of body |
| Material: |
| Steel comp 4130 or steel comp 4140 or steel comp e4340 |
| Material Specification: |
| Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-5000 military |
| specification 3rd material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 1, cl 3 federal specification single treatment response |
| Style Designator: |
| Solid, plain, no outside flanges |
| Specification Data: |
| 26512-g-b10a manufacturers standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |
| Mil-s-6758 spec. |