

View Online at <https://aerobasegroup.com/nsn/3120-00-239-7684>

Shank Diameter:

Between 0.3741 inches and 0.3746 inches

Shank Style:

Hollow, unthreaded

Overall Length:

3.3812 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

Between 0.7400 inches and 0.7850 inches

Bore Center To Shank End Distance:

Between 2.9900 inches and 3.0100 inches

Outer Member Width:

Between 0.2760 inches and 0.2860 inches

Inner Member Width:

Between 0.3700 inches and 0.3750 inches

Shank Inside Diameter:

Between 1.2460 inches and 1.2540 inches

Shank Hole Length:

1.0000 inches

Static Radial Load Rating:

2400 pounds

Hardness Rating:

32.0 rockwell c inner member and 55.0 rockwell c inner member

Special Features:

Shank bore to be offset from center line of rod end 0.0125 in.

Material:

Stainless steel outer race member

Style Designator:

Ball type

Test Data Document:

81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0