

View Online at <https://aerobasegroup.com/nsn/3120-00-239-7684>

**Shank Diameter:**

Between 0.3741 inches and 0.3746 inches

**Shank Style:**

Hollow, unthreaded

**Overall Length:**

3.3812 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Outer Member Outside Diameter:**

Between 0.7400 inches and 0.7850 inches

**Bore Center To Shank End Distance:**

Between 2.9900 inches and 3.0100 inches

**Outer Member Width:**

Between 0.2760 inches and 0.2860 inches

**Inner Member Width:**

Between 0.3700 inches and 0.3750 inches

**Shank Inside Diameter:**

Between 1.2460 inches and 1.2540 inches

**Shank Hole Length:**

1.0000 inches

**Static Radial Load Rating:**

2400 pounds

**Hardness Rating:**

32.0 rockwell c inner member and 55.0 rockwell c inner member

**Special Features:**

Shank bore to be offset from center line of rod end 0.0125 in.

**Material:**

Stainless steel outer race member

**Style Designator:**

Ball type

**Test Data Document:**

81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0