NSN 3120-00-283-2716

Sleeve Bushing - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/3120-00-263-2716 |
|---|
| Hole Diameter: |
| 0.0810 inches first and 0.0860 inches first |
| Overall Length: |
| 1.8400 inches |
| Body Outside Diameter: |
| Between 1.0643 inches and 1.0650 inches |
| Body Inside Diameter: |
| Between 0.8745 inches and 0.8755 inches |
| Flange Outside Diameter: |
| 1.7500 inches |
| Flange Width: |
| Between 0.0610 inches and 0.0620 inches |
| Right Internal Flange Hole Diameter: |
| 0.5620 inches |
| Right Internal Flange Width: |
| 0.0600 inches |
| Lubricant Accommodation Style: |
| Grooved circular |
| Corner Shape: |
| Square outside right corner |
| Surface Finish: |
| 63.0 microinches inside diameter surface of body |
| Antirotation/lubrication Type And Quantity: |
| 4 hole |
| Surface Groove Location And Quantity: |
| 1 external |
| Material: |
| Copper alloy 172 |
| Material Specification: |
| Qq-c-530, temper h federal specification single material response |
| Surface Treatment: |
| Cadmium outside diameter surface of body |
| Surface Treatment Specification: |
| Ps13101, type 2, class 3 mfr ref single treatment response outside diameter surface of body |
| Style Designator: |
| Solid, external flange one end, internal flange one end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 3120-00-283-2716

Sleeve Bushing - Page 2 of 2



Fiig:

A045a0