NSN 3120-00-287-9729

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-287-9729

| Overall Length: |
|--|
| Between 0.5050 inches and 0.5100 inches |
| Body Outside Diameter: |
| Between 0.4351 inches and 0.4361 inches |
| Body Inside Diameter: |
| Between 0.2495 inches and 0.2510 inches |
| Lubricant Accommodation Style: |
| Grooved circular |
| Corner Shape: |
| Square outside right corner |
| Surface Groove Location And Quantity: |
| 1 external |
| Material: |
| Steel comp 8630 or steel comp 4130 |
| Material Specification: |
| Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Style Designator: |
| Solid, plain, no outside flanges |
| Specification Data: |
| 80205-nas73 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |
| Mil-s-6050 spec. |
| |