## NSN 3120-00-298-1434

Rod End Plain Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-298-1434

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Left-hand  |
| Shank Style:   |
| Externally threaded  |
| Overall Length:  |
| 3.2050 inches  |
| Bore Diameter:   |
| Between 0.3745 inches and 0.3750 inches  |
| Outer Member Outside Diameter:   |
| 1.0900 inches  |
| Bore Center To Shank End Distance:   |
| 2.6600 inches  |
| Outer Member Width:  |
| Between 0.4110 inches and 0.4210 inches  |
| Inner Member Width:  |
| Between 0.4980 inches and 0.5000 inches  |
| Shank Thread Length:   |
| 1.2000 inches  |
| Thread Diameter:   |
| 0.625 inches   |
| Thready Qty Per Inch (tpi):  |
| 18   |
| Special Features:  |
| Keyway in shank, shank drilled through end 0.3125 in. Diameter by 0.5600 in.           |
| Material:  |
| Steel comp 630 race insert or steel comp 631 race insert or steel comp 410 race insert |
| Style Designator:  |
| Ball type  |
| Thread Series Designator:  |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A045a0   |
|  |
|  |