

View Online at <https://aerobasegroup.com/nsn/3120-00-315-6114>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

4.5938 inches

Bore Diameter:

0.8750 inches

Outer Member Outside Diameter:

Between 0.9062 inches and 0.9687 inches

Bore Center To Shank End Distance:

3.6876 inches

Outer Member Width:

0.6560 inches

Inner Member Width:

Between 0.7600 inches and 0.7650 inches

Shank Thread Length:

2.4375 inches

Static Radial Load Rating:

76250 pounds

Thread Diameter:

0.625 inches

Features Provided:

External lubrication fitting

Thready Qty Per Inch (tpi):

18

Hardness Rating:

60.0 rockwell c race insert and 63.0 rockwell c race insert

Lubrication Feature:

Perforation inner member

Special Features:

Keyway on shank 0.1240 in. Min, 0.1270 in. Maximum w, 0.830in. Min, 0.0903 in. Maximum deep, 2.0000 in. Lg

Material:

Steel comp e52100 race insert

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0