

View Online at <https://aerobasegroup.com/nsn/3120-00-316-5583>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 3.8450 inches and 3.8850 inches

**Bore Diameter:**

Between 0.6245 inches and 0.6250 inches

**Outer Member Outside Diameter:**

Between 1.6000 inches and 1.6200 inches

**Bore Center To Shank End Distance:**

Between 3.0500 inches and 3.0700 inches

**Outer Member Width:**

Between 0.5620 inches and 0.5720 inches

**Inner Member Width:**

Between 0.7480 inches and 0.7500 inches

**Shank Thread Length:**

1.9800 inches

**Static Radial Load Rating:**

39000 pounds

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

16

**Special Features:**

Keyway in shank 1.5200 in. Lg, shank drilled through end 0.3750 in. Diameter 1.6500 in. Deep, inspection hole in shank 0.0690 in. Min 0.0740 in. Maximum dia1.3800 in. Center to end

**Material:**

Steel comp 631 race insert or steel comp 630 race insert or steel comp 410 race insert

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0