

View Online at <https://aerobasegroup.com/nsn/3120-00-316-5583>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 3.8450 inches and 3.8850 inches

Bore Diameter:

Between 0.6245 inches and 0.6250 inches

Outer Member Outside Diameter:

Between 1.6000 inches and 1.6200 inches

Bore Center To Shank End Distance:

Between 3.0500 inches and 3.0700 inches

Outer Member Width:

Between 0.5620 inches and 0.5720 inches

Inner Member Width:

Between 0.7480 inches and 0.7500 inches

Shank Thread Length:

1.9800 inches

Static Radial Load Rating:

39000 pounds

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Special Features:

Keyway in shank 1.5200 in. Lg, shank drilled through end 0.3750 in. Diameter 1.6500 in. Deep, inspection hole in shank 0.0690 in. Min 0.0740 in. Maximum dia1.3800 in. Center to end

Material:

Steel comp 631 race insert or steel comp 630 race insert or steel comp 410 race insert

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0