NSN 3120-00-316-6032

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-316-6032

Overall Length: Between 0.3290 inches and 0.3340 inches Body Outside Diameter: Between 0.5632 inches and 0.5637 inches Body Inside Diameter: Between 0.4372 inches and 0.5637 inches Body Inside Diameter: Between 0.4372 inches and 0.4382 inches Corner Shape: Square all corners Hardness Rating: 39.0 rockwell c and 42.0 rockwell c Surface Finish: 125.0 microinches intermediate layer Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificati format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Between 0.5632 inches and 0.5637 inches Body Inside Diameter: Between 0.4372 inches and 0.4382 inches Corner Shape: Square all corners Hardness Rating: 39.0 rockwell c and 42.0 rockwell c Surface Finish: 125.0 microinches intermediate layer Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Between 0.5632 inches and 0.5637 inches Body Inside Diameter: Between 0.4372 inches and 0.4382 inches Corner Shape: Square all corners Hardness Rating: 39.0 rockwell c and 42.0 rockwell c Surface Finish: 125.0 microinches intermediate layer Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Between 0.4372 inches and 0.4382 inches Corner Shape: Square all corners Hardness Rating: 39.0 rockwell c and 42.0 rockwell c Surface Finish: 125.0 microinches intermediate layer Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Between 0.4372 inches and 0.4382 inches Corner Shape: Square all corners Hardness Rating: 39.0 rockwell c and 42.0 rockwell c Surface Finish: 125.0 microinches intermediate layer Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Corner Shape: Square all corners Hardness Rating: 39.0 rockwell c and 42.0 rockwell c Surface Finish: 125.0 microinches intermediate layer Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Square all corners Hardness Rating: 39.0 rockwell c and 42.0 rockwell c Surface Finish: 125.0 microinches intermediate layer Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Hardness Rating: 39.0 rockwell c and 42.0 rockwell c Surface Finish: 125.0 microinches intermediate layer Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
39.0 rockwell c and 42.0 rockwell c Surface Finish: 125.0 microinches intermediate layer Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificati format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Surface Finish: 125.0 microinches intermediate layer Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificati format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Material: Steel comp 4340 Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Strace Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificati format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Surface Treatment: Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificati format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Cadmium and chromate Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Style Designator: Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificati format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Solid, plain, no outside flanges Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificati format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a
Shelf Life: N/a
N/a
Heit Of Magazina
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0