

View Online at <https://aerobasegroup.com/nsn/3120-00-324-7343>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 3.7350 inches and 3.7650 inches

Bore Diameter:

Between 0.7495 inches and 0.7515 inches

Lubrication Material:

Grease, mil-g-23827

Outer Member Outside Diameter:

Between 1.7400 inches and 1.7600 inches

Bore Center To Shank End Distance:

Between 2.8650 inches and 2.8850 inches

Outer Member Width:

Between 0.6350 inches and 0.6450 inches

Inner Member Width:

Between 0.8700 inches and 0.8750 inches

Shank Thread Length:

Between 1.7182 inches and 1.8125 inches

Static Radial Load Rating:

19000 pounds

Thread Diameter:

0.750 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

16

Special Features:

Keyway in shank for standard nas 513 lockwasher

Style Designator:

Ball type

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0