

View Online at <https://aerobasegroup.com/nsn/3120-00-325-6235>

Hole Diameter:

0.3120 inches first

Overall Length:

Between 2.7490 inches and 2.7510 inches

Body Outside Diameter:

Between 2.8070 inches and 2.8270 inches

Body Inside Diameter:

Between 2.6164 inches and 2.6374 inches

Lubrication Material:

Lubricating oil

Left Flange Outside Diameter:

Between 3.5950 inches and 3.6550 inches

Right Flange Outside Diameter:

Between 3.5950 inches and 3.6550 inches

Left Flange Width:

Between 0.1010 inches and 0.1030 inches

Right Flange Width:

Between 0.1010 inches and 0.1030 inches

Distance From Centerline Of Opening To Left End Of Bearing:

1.3750 inches second

Lubricant Accommodation Style:

Grooved circular

Locking Lug Height:

Between 0.0450 inches and 0.0550 inches

Locking Lug Length:

Between 0.1900 inches and 0.2200 inches

Locking Lug Width:

Between 0.1750 inches and 0.1800 inches

Corner Shape:

Square right flange outside left corner

Hole Spacing Angle:

35.0 degrees

Surface Groove Location And Quantity:

1 internal

Distance From Lug End To End Of Bearing:

Between 1.0065 inches and 1.0160 inches

Material:

Steel comp 1010 outer layer

Material Specification:

Sae 49 assn standard single material response inner layer

Surface Treatment:

Tin

Style Designator:

Half sleeve, external flanges both ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0