## NSN 3120-00-325-6235

Sleeve Bearing Half - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-325-6235

**Hole Diameter:** 

0.3120 inches first

**Overall Length:** 

Between 2.7490 inches and 2.7510 inches

**Body Outside Diameter:** 

Between 2.8070 inches and 2.8270 inches

**Body Inside Diameter:** 

Between 2.6164 inches and 2.6374 inches

**Lubrication Material:** 

Lubricating oil

Left Flange Outside Diameter:

Between 3.5950 inches and 3.6550 inches

**Right Flange Outside Diameter:** 

Between 3.5950 inches and 3.6550 inches

Left Flange Width:

Between 0.1010 inches and 0.1030 inches

**Right Flange Width:** 

Between 0.1010 inches and 0.1030 inches

Distance From Centerline Of Opening To Left End Of Bearing:

1.3750 inches second

**Lubricant Accommodation Style:** 

Grooved circular

**Locking Lug Height:** 

Between 0.0450 inches and 0.0550 inches

**Locking Lug Length:** 

Between 0.1900 inches and 0.2200 inches

**Locking Lug Width:** 

Between 0.1750 inches and 0.1800 inches

**Corner Shape:** 

Square right flange outside left corner

**Hole Spacing Angle:** 

35.0 degrees

**Surface Groove Location And Quantity:** 

1 internal

**Distance From Lug End To End Of Bearing:** 

Between 1.0065 inches and 1.0160 inches

Material:

Steel comp 1010 outer layer

**Material Specification:** 

Sae 49 assn standard single material response inner layer

**Surface Treatment:** 

Tin

## NSN 3120-00-325-6235

Sleeve Bearing Half - Page 2 of 2



| Sty | le [ | )es | ign | ato | r: |
|-----|------|-----|-----|-----|----|
|     |      |     |     |     |    |

Half sleeve, external flanges both ends

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A045a0