

View Online at <https://aerobasegroup.com/nsn/3120-00-326-4520>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 3.3600 inches and 3.3900 inches

Bore Diameter:

Between 0.6245 inches and 0.6265 inches

Lubrication Material:

Grease, mil-g-23827

Outer Member Outside Diameter:

Between 1.4900 inches and 1.5100 inches

Bore Center To Shank End Distance:

Between 2.6150 inches and 2.6350 inches

Outer Member Width:

Between 0.5720 inches and 0.5820 inches

Inner Member Width:

Between 0.7450 inches and 0.7500 inches

Shank Thread Length:

Between 1.5930 inches and 1.6870 inches

Static Radial Load Rating:

16000 pounds

Thread Diameter:

0.625 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

18

Special Features:

Keyway in shank for standard nas 513 lockwasher

Material:

Steel comp 630 race insert

Surface Treatment:

Cadmium rod end body and chromate rod end body

Style Designator:

Ball type

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0