

View Online at <https://aerobasegroup.com/nsn/3120-00-328-8425>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

4.1900 inches

**Bore Diameter:**

Between 0.4995 inches and 0.5000 inches

**Lubrication Material:**

Grease, mil-g-23827

**Outer Member Outside Diameter:**

1.5000 inches

**Bore Center To Shank End Distance:**

3.4400 inches

**Outer Member Width:**

Between 0.3850 inches and 0.3950 inches

**Inner Member Width:**

Between 0.4950 inches and 0.5000 inches

**Shank Thread Length:**

2.2000 inches

**Static Radial Load Rating:**

13000 pounds

**Thread Diameter:**

0.500 inches

**Features Provided:**

Flush lubrication fitting

**Thready Qty Per Inch (tpi):**

20

**Lubrication Feature:**

Perforation inner member

**Special Features:**

Keyway in shank 2.0600 in. Lg, shank drilled through thd 0.0690 in. Min 0.0740 in. Maximum diameter 1.0400 in. Center to end

**Material:**

Steel comp xm-13 rod end body

**Surface Treatment:**

Cadmium race insert

**Style Designator:**

Ball type

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0