

View Online at <https://aerobasegroup.com/nsn/3120-00-332-3866>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 3.4700 inches and 3.5100 inches

Bore Diameter:

Between 0.4370 inches and 0.4375 inches

Outer Member Outside Diameter:

Between 1.2500 inches and 1.2700 inches

Bore Center To Shank End Distance:

Between 2.8500 inches and 2.8700 inches

Outer Member Width:

Between 0.4370 inches and 0.4470 inches

Inner Member Width:

Between 0.5600 inches and 0.5620 inches

Shank Thread Length:

2.0560 inches

Static Radial Load Rating:

20700 pounds

Thread Diameter:

0.562 inches

Thready Qty Per Inch (tpi):

18

Special Features:

Inspection hole in shank 1.1260 in. From center to end of shank, keyway in shank 1.7600 in. Lg

Material:

Steel comp 631 race insert or steel comp 630 race insert or steel comp 410 race insert

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0