

View Online at <https://aerobasegroup.com/nsn/3120-00-374-9714>

**Hole Diameter:**

0.2400 inches and 0.2600 inches first

**Overall Length:**

Between 2.2490 inches and 2.2510 inches

**Body Outside Diameter:**

3.0670 inches

**Body Inside Diameter:**

Between 2.8764 inches and 2.8794 inches

**Left Flange Outside Diameter:**

Between 3.8770 inches and 3.9710 inches

**Right Flange Outside Diameter:**

Between 3.8770 inches and 3.9710 inches

**Left Flange Width:**

Between 0.1010 inches and 0.1030 inches

**Right Flange Width:**

Between 0.1010 inches and 0.1030 inches

**Distance From Centerline Of Opening To Left End Of Bearing:**

1.1140 inches and 1.1360 inches first

**Lubricant Accommodation Style:**

Grooved circular

**Locking Lug Height:**

Between 0.0450 inches and 0.0550 inches

**Locking Lug Length:**

Between 0.1900 inches and 0.2200 inches

**Locking Lug Width:**

Between 0.1750 inches and 0.1800 inches

**Corner Shape:**

Square right flange outside left corner

**Antirotation/lubrication Type And Quantity:**

2 hole

**Hole Spacing Angle:**

35.0 degrees

**Surface Groove Location And Quantity:**

1 internal

**Distance From Lug End To End Of Bearing:**

Between 0.4435 inches and 0.4530 inches

**Material:**

Steel comp 1010 outer layer

**Material Specification:**

Sae 49 assn standard single material response inner layer

**Surface Treatment:**

Tin

**Style Designator:**

Half sleeve, external flanges both ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0