# NSN 3120-00-404-3331

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-404-3331

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 0.8730 inches and 0.8750 inches

#### **Body Outside Diameter:**

Between 1.1200 inches and 1.1300 inches

## **Body Inside Diameter:**

Between 0.9400 inches and 0.9420 inches

#### **Corner Shape:**

Square all corners

#### Hardness Rating:

59.0 rockwell superficial 30-n and 62.0 rockwell superficial 30-n

#### **Surface Finish:**

63.0 microinches inside diameter surface of body

#### **Special Features:**

Id countersunk on both ends, 1.0000 in. Min, 1.0200 in. Maximum dia, 59 degrees min, 61 degrees maximum angle

#### Material:

Steel comp 4130

## **Material Specification:**

Mil-t-6736, type 1, cond n military specification single material response

#### **Surface Treatment:**

Cadmium

## **Surface Treatment Specification:**

Qq-p-416, type 2, cl 1 federal specification single treatment response

#### **Style Designator:**

Solid, plain, no outside flanges

#### Shelf Life:

N/a

## **Unit Of Measure:**

\_

#### Demilitarization:

No

## Fiig:

A045a0

## Mil-std (military Standard):

Mil-t-6736 spec.