# NSN 3120-00-404-3351

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-404-3351

## **Overall Length:**

Between 1.3750 inches and 1.3800 inches

## Body Outside Diameter:

0.4680 inches

## Body Inside Diameter:

Between 0.3750 inches and 0.3770 inches

## Corner Shape:

Square all corners

## Hardness Rating:

 $39.0\ rockwell\ c$   $% 100\ rockwell\ c$  and  $45.0\ rockwell\ c$ 

## Surface Finish:

125.0 microinches intermediate layer

## Special Features:

Two identical external flanges symmetrically spaced from each end, 0.625 in. Flange od, 0.062 in. Flange w, 0.375 in. Min, 0.377 in.

Maximum end to flange distance, left flange outside left corner and right flange outside right corners undercut, 0.005 in. Undercut d, 0.062 in.

Undercut w, 0.010 in. Undercut radius, left and right flanges inside corners rd, 0.070 in. Radius

#### Material:

Steel comp 630

#### Material Specification:

Ams 5643 assn standard single material response

### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A045a0