## NSN 3120-00-404-9614

Sleeve Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-404-9614

**Hole Diameter:** 

0.0913 inches and 0.0933 inches first

Slot Length:

0.3000 inches and 0.3200 inches first

**Overall Length:** 

Between 1.6750 inches and 1.7050 inches

**Body Outside Diameter:** 

Between 2.4150 inches and 2.4160 inches

**Body Inside Diameter:** 

Between 2.1480 inches and 2.1520 inches

Flange Outside Diameter:

Between 2.6000 inches and 2.6200 inches

Flange Width:

Between 0.2800 inches and 0.3000 inches

Left Internal Flange Hole Diameter:

Between 1.9900 inches and 2.0100 inches

Left Internal Flange Width:

Between 0.0710 inches and 0.0850 inches

**Lubricant Accommodation Style:** 

Grooved circular

**Corner Shape:** 

Square outside left corner

**Features Provided:** 

Casehardened

Hardness Rating:

79.0 rockwell a and 85.0 rockwell a

**Antirotation/lubrication Type And Quantity:** 

3 hole and 3 slot

**Surface Groove Location And Quantity:** 

1 internal

Material:

Steel comp e9310

**Material Specification:** 

Ams 6260 assn standard single material response

**Style Designator:** 

Solid, external flange one end, internal flange one end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

## **NSN 3120-00-404-9614** Sleeve Bushing - Page 2 of 2



Fiig:

A045a0