NSN 3120-00-405-6789

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-405-6789

_				
C	nt.	Wi	A+	h.
•	UL	**	uц	

0.1200 inches and 0.1290 inches first

Slot Length:

0.1870 inches and 0.1970 inches first

Overall Length:

Between 0.9080 inches and 0.9200 inches

Body Outside Diameter:

Between 1.3865 inches and 1.3870 inches

Body Inside Diameter:

Between 1.1255 inches and 1.1260 inches

Flange Outside Diameter:

Between 1.5400 inches and 1.5500 inches

Flange Width:

Between 0.0950 inches and 0.1000 inches

End To Flange Distance:

Between 0.1930 inches and 0.2000 inches

Corner Shape:

Square outside right corner

Antirotation/lubrication Type And Quantity:

4 slot

Left End Body Diameter:

Any acceptable

Right End Body Diameter:

Any acceptable

Special Features:

Depth of slots 0.0250 in.; od left end of flange 1.3700 in. Min, 1.3800 in maximum dia

Material:

Copper alloy 630

Material Specification:

Ams 4640 assn standard single material response

Style Designator:

Solid, external flange

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A045a0