NSN 3120-00-411-0044



Sleeve Bushing - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/3120-00-411-0044 **Overall Length:** Between 0.1820 inches and 0.1970 inches **Body Outside Diameter:** Between 0.5631 inches and 0.5638 inches **Body Inside Diameter:** Between 0.4335 inches and 0.4345 inches Flange Outside Diameter: Between 0.6770 inches and 0.6970 inches Flange Width: Between 0.0570 inches and 0.0620 inches **Corner Shape:** Square left flange outside right corner Hardness Rating: 40.0 rockwell c and 45.0 rockwell c **Surface Finish:** 125.0 microinches intermediate layer **Special Features:** Alternate corner configuration for left flange body corner, undercut, dim., 0.0050 in. Min, 0.0150 in. Maximum w, 0.0050 in. Maximum depth, 0.0020 in. Min, 0.0050 in. Maximum radius Material: Steel comp 4130 **Material Specification:** Mil-s-6758 military specification single material response **Surface Treatment:** Chromium **Surface Treatment Specification:** Mil-s-6758 federal specification single treatment response **Style Designator:**

Solid, external flange one end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.