

View Online at <https://aerobasegroup.com/nsn/3120-00-411-8976>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

Between 1.7900 inches and 1.8700 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

Between 0.9000 inches and 1.0200 inches

Bore Center To Shank End Distance:

Between 1.3400 inches and 1.3600 inches

Outer Member Width:

Between 0.3270 inches and 0.3470 inches

Inner Member Width:

Between 0.4320 inches and 0.4370 inches

Shank Thread Length:

Between 0.7700 inches and 0.8300 inches

Inspection Hole Center To End Distance:

Between 0.3700 inches and 0.4300 inches

Shank Width Across Wrench Flats:

Between 0.4200 inches and 0.4800 inches

Static Radial Load Rating:

10400 pounds

Thread Diameter:

0.312 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

24

Special Features:

Rod end body requires magnetic inspection

Material:

Steel inner member

Surface Treatment:

Chromium inner member

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0