

View Online at <https://aerobasegroup.com/nsn/3120-00-421-2434>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 1.9500 inches and 1.9800 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Outer Member Outside Diameter:**

Between 0.7960 inches and 0.8160 inches

**Bore Center To Shank End Distance:**

Between 1.5520 inches and 1.5720 inches

**Outer Member Width:**

Between 0.3320 inches and 0.3420 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

Between 0.9700 inches and 1.0600 inches

**Thread Diameter:**

0.313 inches

**Thready Qty Per Inch (tpi):**

24

**Special Features:**

Keyway per nas559 in shank

**Material:**

Stainless steel rod end body

**Material Specification:**

Mil-t-66 aisi 440c/sae 51440c military standard 1st material response inner member

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-t-66 spec.