

View Online at <https://aerobasegroup.com/nsn/3120-00-432-7353>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 3.2400 inches and 3.3200 inches

**Bore Diameter:**

Between 0.3120 inches and 0.3125 inches

**Outer Member Outside Diameter:**

Between 0.9900 inches and 1.0100 inches

**Bore Center To Shank End Distance:**

Between 2.7500 inches and 2.8100 inches

**Outer Member Width:**

Between 0.3720 inches and 0.3820 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

Between 1.2700 inches and 1.3300 inches

**Static Radial Load Rating:**

8000 pounds

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

26.0 rockwell c rod end body and 33.0 rockwell c rod end body

**Special Features:**

Keyway located in shank

**Material:**

Steel rod end body

**Material Specification:**

Mil-s-6758 military specification single material response rod end body

**Surface Treatment:**

Cadmium rod end body

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response rod end body

**Style Designator:**

Ball type

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-6758 spec.