

View Online at <https://aerobasegroup.com/nsn/3120-00-433-4774>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

Between 1.7710 inches and 1.7910 inches

Bore Diameter:

Between 0.2495 inches and 0.2515 inches

Outer Member Outside Diameter:

Between 0.8020 inches and 0.8220 inches

Bore Center To Shank End Distance:

Between 1.3650 inches and 1.3850 inches

Outer Member Width:

0.3090 inches

Inner Member Width:

Between 0.4320 inches and 0.4370 inches

Shank Thread Length:

Between 0.7190 inches and 0.8120 inches

Inspection Hole Center To End Distance:

Between 0.3070 inches and 0.3170 inches

Shank Width Across Wrench Flats:

0.3750 inches

Thread Diameter:

0.250 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

28

Lubrication Feature:

Groove external inner member

Material:

Steel outer race member

Material Specification:

66 federal standard single material response inner member

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0