

View Online at <https://aerobasegroup.com/nsn/3120-00-433-5605>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

Between 4.1050 inches and 4.1450 inches

Bore Diameter:

Between 0.8745 inches and 0.8765 inches

Outer Member Outside Diameter:

Between 1.9900 inches and 2.0100 inches

Bore Center To Shank End Distance:

Between 3.1150 inches and 3.1350 inches

Outer Member Width:

Between 0.7600 inches and 0.7700 inches

Inner Member Width:

Between 0.8700 inches and 0.8750 inches

Shank Thread Length:

Between 1.5940 inches and 1.6870 inches

Inspection Hole Center To End Distance:

Between 0.9270 inches and 0.9470 inches

Shank Width Across Wrench Flats:

Between 1.1150 inches and 1.1350 inches

Static Radial Load Rating:

30000 pounds

Thread Diameter:

0.875 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

14

Special Features:

0.1560 in. Min, 0.1610 in. Maximum wide, 0.0980 in. Min, 0.1030 in. Maximum depth slot in shank end

Material:

Stainless steel race insert

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A045a0