

View Online at <https://aerobasegroup.com/nsn/3120-00-435-0421>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

2.2910 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2515 inches

**Outer Member Outside Diameter:**

Between 1.0730 inches and 1.0930 inches

**Bore Center To Shank End Distance:**

Between 1.7180 inches and 1.7810 inches

**Outer Member Width:**

Between 0.3020 inches and 0.3220 inches

**Inner Member Width:**

Between 0.4950 inches and 0.5000 inches

**Shank Thread Length:**

0.9680 inches

**Static Radial Load Rating:**

7300 pounds

**Thread Diameter:**

0.375 inches

**Features Provided:**

Flush lubrication fitting

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

26.0 rockwell c inner member

**Special Features:**

Standard nas 559 keyway in shank

**Material:**

Steel comp e52100 inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0