

View Online at <https://aerobasegroup.com/nsn/3120-00-441-5405>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

4.2000 inches

Bore Diameter:

Between 0.6245 inches and 0.6250 inches

Lubrication Material:

Grease

Outer Member Outside Diameter:

1.6000 inches

Bore Center To Shank End Distance:

3.4000 inches

Outer Member Width:

Between 0.5200 inches and 0.5300 inches

Inner Member Width:

Between 0.6200 inches and 0.6250 inches

Shank End To Shoulder Length:

2.3900 inches

Shank Thread Length:

2.1800 inches

Shank Inside Diameter:

0.2970 inches

Shank Hole Length:

1.6000 inches

Static Radial Load Rating:

20000 pounds

Thread Diameter:

0.875 inches

Features Provided:

External lubrication fitting

Thready Qty Per Inch (tpi):

14

Hardness Rating:

38.8 rockwell c rod end body and 42.7 rockwell c rod end body

Lubrication Feature:

Groove internal inner member and perforation internal inner member

Special Features:

Keyway rod end

Material:

Stainless steel rod end body

Surface Treatment:

Cadmium rod end body

Style Designator:

Shouldered ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A045a0