

View Online at <https://aerobasegroup.com/nsn/3120-00-441-5407>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

4.0300 inches

Bore Diameter:

Between 0.4995 inches and 0.5000 inches

Lubrication Material:

Grease

Outer Member Outside Diameter:

1.3800 inches

Bore Center To Shank End Distance:

3.3400 inches

Outer Member Width:

Between 0.3950 inches and 0.4150 inches

Inner Member Width:

Between 0.4950 inches and 0.5000 inches

Shank End To Shoulder Length:

2.3700 inches

Shank Thread Length:

2.1230 inches

Static Radial Load Rating:

112000 pounds

Thread Diameter:

0.625 inches

Features Provided:

External lubrication fitting

Thready Qty Per Inch (tpi):

18

Hardness Rating:

38.8 rockwell c rod end body and 42.7 rockwell c rod end body

Lubrication Feature:

Groove internal inner member and perforation internal inner member

Special Features:

Keyway rod end

Material:

Stainless steel rod end body

Surface Treatment:

Cadmium rod end body

Style Designator:

Shouldered ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A045a0