

View Online at <https://aerobasegroup.com/nsn/3120-00-441-5446>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

3.8900 inches

**Taper Length:**

0.1450 inches

**Bore Diameter:**

Between 0.5620 inches and 0.5625 inches

**Lubrication Material:**

Grease

**Outer Member Outside Diameter:**

1.5000 inches

**Bore Center To Shank End Distance:**

3.1400 inches

**Outer Member Width:**

Between 0.4420 inches and 0.4620 inches

**Inner Member Width:**

Between 0.5570 inches and 0.5620 inches

**Shank End To Shoulder Length:**

1.8750 inches

**Shank Thread Length:**

0.8500 inches

**Static Radial Load Rating:**

29400 pounds

**Thread Diameter:**

0.812 inches

**Features Provided:**

External lubrication fitting

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

32.2 rockwell c rod end body and 38.8 rockwell c rod end body

**Lubrication Feature:**

Groove outer race member and perforation outer race member

**Material:**

Stainless steel outer race member

**Material Specification:**

Mil-s-5000 cond c2 military specification 2nd material response rod end body

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type with flare

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5000 spec.