

View Online at <https://aerobasegroup.com/nsn/3120-00-441-5446>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

3.8900 inches

Taper Length:

0.1450 inches

Bore Diameter:

Between 0.5620 inches and 0.5625 inches

Lubrication Material:

Grease

Outer Member Outside Diameter:

1.5000 inches

Bore Center To Shank End Distance:

3.1400 inches

Outer Member Width:

Between 0.4420 inches and 0.4620 inches

Inner Member Width:

Between 0.5570 inches and 0.5620 inches

Shank End To Shoulder Length:

1.8750 inches

Shank Thread Length:

0.8500 inches

Static Radial Load Rating:

29400 pounds

Thread Diameter:

0.812 inches

Features Provided:

External lubrication fitting

Thready Qty Per Inch (tpi):

20

Hardness Rating:

32.2 rockwell c rod end body and 38.8 rockwell c rod end body

Lubrication Feature:

Groove outer race member and perforation outer race member

Material:

Stainless steel outer race member

Material Specification:

Mil-s-5000 cond c2 military specification 2nd material response rod end body

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type with flare

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.