## NSN 3120-00-441-9814

Sleeve Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-441-9814

Overall Length:0.4688 inchesBody Outside Diameter:Between 0.5560 inches and 0.5565 inchesBody Inside Diameter:Between 0.3749 inches and 0.3754 inchesFlange Outside Diameter:Between 0.7994 inches and 0.7998 inchesFlange Width:Between 0.2415 inches and 0.2420 inchesLubricant Accommodation Style:Grooved open both endsCorner Shape:Square outside right cornerSurface Finish:20.0 microinches inside diameter surface of bodySurface Groove Location And Quantity:2 internalSpecial Features:One side of flange flatted to 0.3910 to 0.4007 in.Surface Treatment:Lead inside diameter surface of bodyStyle Designator:Solid, external flange one end
Body Outside Diameter:Between 0.5560 inches and 0.5565 inchesBody Inside Diameter:Between 0.3749 inches and 0.3754 inchesFlange Outside Diameter:Between 0.7994 inches and 0.7998 inchesFlange Width:Between 0.2415 inches and 0.2420 inchesLubricant Accommodation Style:Grooved open both endsCorner Shape:Square outside right cornerSurface Finish:20.0 microinches inside diameter surface of bodySurface Groove Location And Quantity:2 internalSpecial Features:One side of flange flatted to 0.3910 to 0.4007 in.Surface Treatment:Lead inside diameter surface of bodyStyle Designator:
Between 0.5560 inches and 0.5565 inchesBody Inside Diameter:Between 0.3749 inches and 0.3754 inchesFlange Outside Diameter:Between 0.7994 inches and 0.7998 inchesFlange Width:Between 0.2415 inches and 0.2420 inchesLubricant Accommodation Style:Grooved open both endsCorner Shape:Square outside right cornerSurface Finish:20.0 microinches inside diameter surface of bodySurface Groove Location And Quantity:2 internalSpecial Features:One side of flange flatted to 0.3910 to 0.4007 in.Surface Treatment:Lead inside diameter surface of bodyStyle Designator:
Body Inside Diameter:Between 0.3749 inches and 0.3754 inchesFlange Outside Diameter:Between 0.7994 inches and 0.7998 inchesFlange Width:Between 0.2415 inches and 0.2420 inchesLubricant Accommodation Style:Grooved open both endsCorner Shape:Square outside right cornerSurface Finish:20.0 microinches inside diameter surface of bodySurface Groove Location And Quantity:2 internalSpecial Features:One side of flange flatted to 0.3910 to 0.4007 in.Surface Treatment:Lead inside diameter surface of bodyStyle Designator:
Between 0.3749 inches and 0.3754 inchesFlange Outside Diameter:Between 0.7994 inches and 0.7998 inchesFlange Width:Between 0.2415 inches and 0.2420 inchesLubricant Accommodation Style:Grooved open both endsCorner Shape:Square outside right cornerSurface Finish:20.0 microinches inside diameter surface of bodySurface Groove Location And Quantity:2 internalSpecial Features:One side of flange flatted to 0.3910 to 0.4007 in.Surface Treatment:Lead inside diameter surface of bodyStyle Designator:
Flange Outside Diameter: Between 0.7994 inches and 0.7998 inches Flange Width: Between 0.2415 inches and 0.2420 inches Lubricant Accommodation Style: Grooved open both ends Corner Shape: Square outside right corner Surface Finish: 20.0 microinches inside diameter surface of body Surface Groove Location And Quantity: 2 internal Special Features: One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
Between 0.7994 inches and 0.7998 inchesFlange Width:Between 0.2415 inches and 0.2420 inchesLubricant Accommodation Style:Grooved open both endsCorner Shape:Square outside right cornerSurface Finish:20.0 microinches inside diameter surface of bodySurface Groove Location And Quantity:2 internalSpecial Features:One side of flange flatted to 0.3910 to 0.4007 in.Surface Treatment:Lead inside diameter surface of bodyStyle Designator:
Flange Width:Between 0.2415 inches and 0.2420 inchesLubricant Accommodation Style:Grooved open both endsCorner Shape:Square outside right cornerSurface Finish:20.0 microinches inside diameter surface of bodySurface Groove Location And Quantity:2 internalSpecial Features:One side of flange flatted to 0.3910 to 0.4007 in.Surface Treatment:Lead inside diameter surface of bodyStyle Designator:
Between 0.2415 inches and 0.2420 inches Lubricant Accommodation Style: Grooved open both ends Corner Shape: Square outside right corner Surface Finish: 20.0 microinches inside diameter surface of body Surface Groove Location And Quantity: 2 internal Special Features: One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
Lubricant Accommodation Style: Grooved open both ends Corner Shape: Square outside right corner Surface Finish: 20.0 microinches inside diameter surface of body Surface Groove Location And Quantity: 2 internal Special Features: One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
Grooved open both ends Corner Shape: Square outside right corner Surface Finish: 20.0 microinches inside diameter surface of body Surface Groove Location And Quantity: 2 internal Special Features: One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
Corner Shape: Square outside right corner Surface Finish: 20.0 microinches inside diameter surface of body Surface Groove Location And Quantity: 2 internal Special Features: One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
Square outside right corner Surface Finish: 20.0 microinches inside diameter surface of body Surface Groove Location And Quantity: 2 internal Special Features: One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
Surface Finish: 20.0 microinches inside diameter surface of body Surface Groove Location And Quantity: 2 internal Special Features: One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
20.0 microinches inside diameter surface of body Surface Groove Location And Quantity: 2 internal Special Features: One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
Surface Groove Location And Quantity: 2 internal Special Features: One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
2 internal <b>Special Features:</b> One side of flange flatted to 0.3910 to 0.4007 in. <b>Surface Treatment:</b> Lead inside diameter surface of body <b>Style Designator:</b>
Special Features: One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
One side of flange flatted to 0.3910 to 0.4007 in. Surface Treatment: Lead inside diameter surface of body Style Designator:
Surface Treatment: Lead inside diameter surface of body Style Designator:
Lead inside diameter surface of body Style Designator:
Style Designator:
Solid external flance one end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0