NSN 3120-00-465-5467

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-465-5467

O,	/era	ш	l ۵n	ath	٠.
U١	/eia		Len	uu	ı.

Between 1.1420 inches and 1.1570 inches

Body Outside Diameter:

Between 0.6882 inches and 0.6882 inches and 0.6892 inches 0.6892 inches

Body Inside Diameter:

Between 0.5625 inches and 0.5625 inches and 0.5640 inches 0.5640 inches

Flange Outside Diameter:

Between 0.8020 inches and 0.8220 inches

Flange Width:

Between 0.0570 inches and 0.0570 inches and 0.0620 inches 0.0620 inches

Corner Shape:

Undercut left flange body corner

Surface Finish:

100.0 microinches intermediate layer100.0 microinches intermediate layer

Steel comp 8630 or steel comp 4130

Material Specification:

Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Style Designator:

Solid, external flange one end

Specification Data:

80205-nas77 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6050 spec.