

View Online at <https://aerobasegroup.com/nsn/3120-00-470-9151>

Thread Class:

3b

Thread Direction:

Left-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

3.2500 inches

Bore Diameter:

Between 0.6245 inches and 0.6275 inches

Outer Member Outside Diameter:

1.5000 inches

Bore Center To Shank End Distance:

2.5000 inches

Outer Member Width:

0.5620 inches

Inner Member Width:

0.7500 inches

Shank Thread Length:

1.5000 inches

Inspection Hole Center To End Distance:

0.7500 inches

Shank Width Across Wrench Flats:

0.8750 inches

Static Radial Load Rating:

8060 pounds

Thread Diameter:

0.625 inches

Features Provided:

External lubrication fitting and screw plug closure fitting

Thready Qty Per Inch (tpi):

18

Hardness Rating:

60.0 rockwell c inner member

Lubrication Feature:

Groove internal outer member

Special Features:

Inspection hole 0.0625 in. Dia

Material:

Steel comp e51100 inner member

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0