

View Online at <https://aerobasegroup.com/nsn/3120-00-472-2995>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

3.3750 inches

**Bore Diameter:**

Between 0.6245 inches and 0.6265 inches

**Outer Member Outside Diameter:**

Between 1.4900 inches and 1.5100 inches

**Bore Center To Shank End Distance:**

Between 2.6100 inches and 2.6400 inches

**Outer Member Width:**

Between 0.5570 inches and 0.5670 inches

**Inner Member Width:**

Between 0.7450 inches and 0.7500 inches

**Shank Thread Length:**

Between 1.5937 inches and 1.6875 inches

**Static Radial Load Rating:**

7000 pounds

**Thread Diameter:**

0.625 inches

**Features Provided:**

Flush lubrication fitting

**Thready Qty Per Inch (tpi):**

18

**Lubrication Feature:**

Perforation race insert

**Material:**

Steel rod end body

**Material Specification:**

Ams 7440 assn standard all material responses inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0