## NSN 3120-00-487-8138

Sleeve Bushing - Page 1 of 1

Mil-std (military Standard):

Mil-s-5000 spec.



| view Online at https://aerobasegroup.com/nsn/3120-00-467-6136   |
|---|
| Overall Length:   |
| Between 0.8650 inches and 0.8850 inches   |
| Body Outside Diameter:  |
| Between 0.9383 inches and 0.9393 inches   |
| Body Inside Diameter:   |
| Between 0.7500 inches and 0.7515 inches   |
| Left Internal Flange Hole Diameter:   |
| Between 0.3750 inches and 0.3755 inches   |
| Left Internal Flange Width:   |
| Between 0.0740 inches and 0.1140 inches   |
| Corner Shape:   |
| Square outside right corner   |
| Surface Finish:   |
| 63.0 microinches outside diameter surface of body   |
| Material:   |
| Steel   |
| Material Specification:   |
| Mil-s-5000 military standard all material responses   |
| Surface Treatment:  |
| Cadmium   |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, cl 3 federal specification single treatment response  |
| Style Designator:   |
| Solid, plain, no outside flanges, internal flange one end   |
| Test Data Document:   |
| 81205-bac5424 cl b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain           |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                             |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A045a0  |