NSN 3120-00-503-6022

Sleeve Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-503-6022

HOI	e D	ıam	ete	r:
0.0	450	:		

0.0450 inches and 0.0550 inches first

Overall Length:

Between 0.9280 inches and 0.9380 inches

Body Outside Diameter:

Between 0.9394 inches and 0.9401 inches

Body Inside Diameter:

Between 0.7500 inches and 0.7512 inches

Flange Outside Diameter:

Between 1.1156 inches and 1.1356 inches

Flange Width:

Between 0.0923 inches and 0.0963 inches

Lubricant Accommodation Style:

Grooved circular

Corner Shape:

Square outside right corner

Surface Finish:

63.0 microinches outside diameter surface of body

Antirotation/lubrication Type And Quantity:

4 hole

Surface Groove Location And Quantity:

1 internal and 1 external

Material:

Copper alloy 630

Material Specification:

Ams 4660 assn standard single material response or ams 4880 assn standard single material response

Surface Treatment:

Cadmium and chromate right end surface of left flange

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response right end surface of left flange

Style Designator:

Solid, external flange one end

Specification Data:

36659-ls11164 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0