NSN 3120-00-503-6027

Sleeve Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-503-6027

		_					
Hol	_	11	12	m	Δi	-Δ	r-
IIV		$\mathbf{\nu}$	ıa		CI	. 🕶	

0.0450 inches and 0.0550 inches first

Overall Length:

Between 0.2710 inches and 0.2810 inches

Body Outside Diameter:

Between 0.6268 inches and 0.6274 inches

Body Inside Diameter:

Between 0.5000 inches and 0.5010 inches

Flange Outside Diameter:

Between 0.7406 inches and 0.7606 inches

Flange Width:

Between 0.0603 inches and 0.0643 inches

Lubricant Accommodation Style:

Grooved circular

Corner Shape:

Square outside right corner

Surface Finish:

63.0 microinches outside diameter surface of body

Antirotation/lubrication Type And Quantity:

2 hole

Surface Groove Location And Quantity:

1 internal and 1 external

Material:

Copper alloy 630

Material Specification:

Ams 4660 assn standard single material response or ams 4880 assn standard single material response

Surface Treatment:

Cadmium and chromate right end surface of left flange

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response right end surface of left flange

Style Designator:

Solid, external flange one end

Specification Data:

36659-ls11164 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0