# NSN 3120-00-516-1906

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-516-1906

## **Overall Length:**

Between 0.1820 inches and 0.1970 inches

## **Body Outside Diameter:**

Between 0.5006 inches and 0.5013 inches

## **Body Inside Diameter:**

Between 0.3750 inches and 0.3765 inches

## Flange Outside Diameter:

Between 0.6150 inches and 0.6350 inches

### Flange Width:

Between 0.0570 inches and 0.0620 inches

## Corner Shape:

Undercut left flange body corner

### Surface Finish:

100.0 microinches intermediate layer

### Material:

Steel comp 8630 or steel comp 4130

## **Material Specification:**

Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response

## Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## Style Designator:

Solid, external flange one end

## **Specification Data:**

80205-nas77 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

Fiig:

#### A045a0

Mil-std (military Standard):

Mil-s-6050 spec.