# NSN 3120-00-516-1913

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-516-1913

## **Overall Length:**

Between 0.5220 inches and 0.5370 inches

## Body Outside Diameter:

Between 0.5006 inches and 0.5013 inches

## Body Inside Diameter:

Between 0.3750 inches and 0.3765 inches

## Flange Outside Diameter:

Between 0.6150 inches and 0.6350 inches

## Flange Width:

Between 0.0570 inches and 0.0620 inches

## Corner Shape:

Undercut left flange body corner

## Surface Finish:

100.0 microinches intermediate layer

## **Special Features:**

Id and od to be parallel and concentric within 0.0030 tir

#### Material:

Steel comp 4130 or steel comp 8630

#### Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### Style Designator:

Solid, external flange one end

#### **Specification Data:**

80205-nas77 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

```
--
```

## Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.