NSN 3120-00-516-9619



Sleeve Bearing - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3120-00-516-9619 **Hole Diameter:** 0.1562 inches first **Slot Width:** Any acceptable first Slot Length: Any acceptable first **Overall Length:** Between 1.3900 inches and 1.4100 inches **Body Outside Diameter:** Between 3.5380 inches and 3.5480 inches **Body Inside Diameter:** Between 3.4460 inches and 3.4480 inches Left Flange Outside Diameter: Between 3.5840 inches and 3.5860 inches **Right Flange Outside Diameter:** Between 3.5840 inches and 3.5860 inches Left Flange Width: Between 0.3900 inches and 0.4100 inches Right Flange Width: Between 0.3900 inches and 0.4100 inches **Lubricant Accommodation Style:** Grooved double figure 8 **Corner Shape:** Square all corners **Surface Finish:** 63.0 microinches **Antirotation/lubrication Type And Quantity:** 4 hole and 2 slot Material: Copper alloy 934 **Material Specification:** Mil-b-16261 gr 8 cl 1 military specification single material response **Style Designator:** Solid, external flanges both ends Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A045a0

NSN 3120-00-516-9619

Sleeve Bearing - Page 2 of 2



Mil-std (military Standard):

Mil-b-16261 spec.