

View Online at <https://aerobasegroup.com/nsn/3120-00-528-5739>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

2.4380 inches

**Bore Diameter:**

Between 0.3745 inches and 0.3765 inches

**Outer Member Outside Diameter:**

1.0000 inches

**Bore Center To Shank End Distance:**

1.9380 inches

**Outer Member Width:**

0.4110 inches

**Inner Member Width:**

Between 0.4950 inches and 0.5000 inches

**Shank Thread Length:**

1.2500 inches

**Thread Diameter:**

0.438 inches

**Features Provided:**

External lubrication fitting and screw plug closure fitting

**Thready Qty Per Inch (tpi):**

20

**Lubrication Feature:**

Groove external inner member

**Special Features:**

Magnaflux inspected; stamped with letter m

**Material:**

Steel outer race member

**Material Specification:**

66 federal standard single material response inner member

**Surface Treatment:**

Cadmium outer race member

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Reference Number Differentiating Characteristics:**

As differentiated by features

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0