## NSN 3120-00-528-6602

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-528-6602
Overall Length:
Between 0.5320 inches and 0.5470 inches
Body Outside Diameter:
Between 0.5006 inches and 0.5013 inches
Body Inside Diameter:
Between 0.3750 inches and 0.3765 inches
Flange Outside Diameter:
Between 0.6150 inches and 0.6350 inches
Flange Width:
Between 0.0570 inches and 0.0620 inches
Corner Shape:
Undercut left flange body corner
Surface Finish:
100.0 microinches intermediate layer
Special Features:
Id and od to be parallel and concentric within 0.0030 tir
Material:
Steel comp 4130 or steel comp 8630
Material Specification:
Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Style Designator:
Solid, external flange one end
Specification Data:
80205-nas77 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0

Mil-s-6758 spec.

Mil-std (military Standard):