# NSN 3120-00-528-6626

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-528-6626

### **Overall Length:**

Between 0.5550 inches and 0.5650 inches

### **Body Outside Diameter:**

Between 0.5631 inches and 0.5638 inches

## **Body Inside Diameter:**

Between 0.4375 inches and 0.4390 inches

### Flange Outside Diameter:

Between 0.6770 inches and 0.6970 inches

#### Flange Width:

Between 0.0570 inches and 0.0620 inches

### **Corner Shape:**

Undercut left flange body corner

### Surface Finish:

100.0 microinches intermediate layer

#### **Special Features:**

Id and od to be parallel and concentric within 0.0030 tir

### Material:

Steel comp 4130 or steel comp 8630

### **Material Specification:**

Mil-s-6798 military specification 1st material response or mil-s-6050 military specification 2nd material response

# Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## Style Designator:

Solid, external flange one end

### **Specification Data:**

80205-nas77 professional/industrial association standard

#### Shelf Life:

N/a

### Unit Of Measure:

```
--
```

# Demilitarization:

No

Fiig:

### A045a0

Mil-std (military Standard):

Mil-s-6798 spec.