## NSN 3120-00-530-6694

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-530-6694

Overal	م ا اا	natk	١.
Overa	II LC	HULL	ı.

Between 0.6376 inches and 0.6436 inches

**Body Outside Diameter:** 

Between 0.6260 inches and 0.6265 inches

**Body Inside Diameter:** 

Between 0.4834 inches and 0.4844 inches

Flange Outside Diameter:

Between 0.7400 inches and 0.7600 inches

Flange Width:

Between 0.0615 inches and 0.0625 inches

**Corner Shape:** 

Undercut left flange body corner

**Hardness Rating:** 

26.0 rockwell c and 33.0 rockwell c

**Surface Finish:** 

32.0 microinches outside diameter surface of body

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp 8630

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, class 2 federal specification single treatment response

**Style Designator:** 

Solid, external flange one end

**Specification Data:** 

97499-22-003 through 22-024 manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A045a0